



## Flight test report: EN



Manufacturer	<b>Apco Aviation Ltd.</b>	Certification number	PG_0359.2010
Address	7, Chalamish St., Industrial park 38900 Caesarea Israel	Date of flight test	15. 07. 2010
Representative	None	Place of test	Villeneuve
Glider model	<b>Fun 42 II</b>	<b>Classification</b>	<b>B</b>
Trimmer	yes: closed		

<b>Test pilot</b>	Thurnheer Claude	Zoller Alain
<b>Harness</b>	Sky Paragliders - Twin	Advance - Bi Pro 2
<b>Total weight in flight (kg)</b>	140	230

Category	Grade	Criteria	Grade	Criteria	Grade
<b>1. Inflation/Take-off</b>	<b>A</b>				
Rising behaviour		Smooth, easy and constant rising	A	Smooth, easy and constant rising	A
Special take off technique required		No	A	No	A
<b>2. Landing</b>	<b>A</b>				
Special landing technique required		No	A	No	A
<b>3. Speed in straight flight</b>	<b>B</b>				
Trim speed more than 30 km/h		Yes	A	Yes	A
Speed range using the controls larger than 10 km/h		Yes	A	Yes	A
Minimum speed		25 km/h to 30 km/h	B	25 km/h to 30 km/h	B
<b>4. Control movement</b>	<b>A</b>				
<i>Max. weight in flight up to 80 kg</i>					
Symmetric control pressure / travel		not available	0	not available	0
<i>Max. weight in flight 80 kg to 100 kg</i>					
Symmetric control pressure / travel		not available	0	not available	0
<i>Max. weight in flight greater than 100 kg</i>					
Symmetric control pressure / travel		Increasing / greater than 65 cm	A	Increasing / greater than 65 cm	A
<b>5. Pitch stability exiting accelerated flight</b>	<b>0</b>				
Dive forward angle on exit		not available	0	not available	0
Collapse occurs		not available	0	not available	0
<b>6. Pitch stability operating controls during accelerated flight</b>	<b>0</b>				
Collapse occurs		not available	0	not available	0
<b>7. Roll stability and damping</b>	<b>A</b>				
Oscillations		Reducing	A	Reducing	A
<b>8. Stability in gentle spirals</b>	<b>A</b>				
Tendency to return to straight flight		Spontaneous exit	A	Spontaneous exit	A
<b>9. Behaviour in a steeply banked turn</b>	<b>B</b>				
Sink rate after two turns		12 m/s to 14 m/s	A	More than 14 m/s	B
<b>10. Symmetric front collapse</b>	<b>B</b>				
Entry		Rocking back less than 45°	A	Rocking back less than 45°	A
Recovery		Spontaneous in less than 3 s	A	Spontaneous in less than 3 s	A
Dive forward angle on exit / Change of course		Dive forward 0° to 30° / Keeping course	A	Dive forward 30° to 60° / Keeping course	B
Cascade occurs		No	A	No	A
<i>With accelerator</i>					
Entry		not available	0	not available	0
Recovery		not available	0	not available	0

Dive forward angle on exit / Change of course	not available	0	not available	0
Cascade occurs	not available	0	not available	0
<b>11. Exiting deep stall (parachutal stall)</b>	<b>A</b>			
Deep stall achieved	Yes	A	Yes	A
Recovery	Spontaneous in less than 3 s	A	Spontaneous in less than 3 s	A
Dive forward angle on exit	Dive forward 0° to 30°	A	Dive forward 0° to 30°	A
Change of course	Changing course less than 45°	A	Changing course less than 45°	A
Cascade occurs	No	A	No	A
<b>12. High angle of attack recovery</b>	<b>A</b>			
Recovery	Spontaneous in less than 3 s	A	Spontaneous in less than 3 s	A
Cascade occurs	No	A	No	A
<b>13. Recovery from a developed full stall</b>	<b>B</b>			
Dive forward angle on exit	Dive forward 0° to 30°	A	Dive forward 30° to 60°	B
Collapse	No collapse	A	No collapse	A
Cascade occurs (other than collapses)	No	A	No	A
Rocking back	Less than 45°	A	Less than 45°	A
Line tension	Most lines tight	A	Most lines tight	A
<b>14. Asymmetric collapse</b>	<b>B</b>			
<i>With 50% collapse</i>				
Change of course until re-inflation / Maximum dive forward or roll angle	Less than 90° / Dive or roll angle 15° to 45°	A	Less than 90° / Dive or roll angle 0° to 15°	A
Re-inflation behaviour	Spontaneous re-inflation	A	Spontaneous re-inflation	A
Total change of course	Less than 360°	A	Less than 360°	A
Collapse on the opposite side occurs	No	A	No	A
Twist occurs	No	A	No	A
Cascade occurs	No	A	No	A
<i>With 75% collapse</i>				
Change of course until re-inflation / Maximum dive forward or roll angle	90° to 180° / Dive or roll angle 15° to 45°	B	90° to 180° / Dive or roll angle 15° to 45°	B
Re-inflation behaviour	Spontaneous re-inflation	A	Spontaneous re-inflation	A
Total change of course	Less than 360°	A	Less than 360°	A
Collapse on the opposite side occurs	No	A	No	A
Twist occurs	No	A	No	A
Cascade occurs	No	A	No	A
<i>With 50% collapse and accelerator</i>				
Change of course until re-inflation / Maximum dive forward or roll angle	not available	0	not available	0
Re-inflation behaviour	not available	0	not available	0
Total change of course	not available	0	not available	0
Collapse on the opposite side occurs	not available	0	not available	0
Twist occurs	not available	0	not available	0
Cascade occurs	not available	0	not available	0
<i>With 75% collapse and accelerator</i>				
Change of course until re-inflation / Maximum dive forward or roll angle	not available	0	not available	0
Re-inflation behaviour	not available	0	not available	0
Total change of course	not available	0	not available	0
Collapse on the opposite side occurs	not available	0	not available	0
Twist occurs	not available	0	not available	0
Cascade occurs	not available	0	not available	0
<b>15. Directional control with a maintained asymmetric collapse</b>	<b>A</b>			
Able to keep course	Yes	A	Yes	A
180° turn away from the collapsed side possible in 10 s	Yes	A	Yes	A
Amount of control range between turn and stall or spin	More than 50 % of the symmetric control travel	A	More than 50 % of the symmetric control travel	A

<b>16. Trim speed spin tendency</b>	<b>A</b>			
Spin occurs	No	A	No	A
<b>17. Low speed spin tendency</b>	<b>A</b>			
Spin occurs	No	A	No	A
<b>18. Recovery from a developed spin</b>	<b>A</b>			
Spin rotation angle after release	Stops spinning in less than 90°	A	Stops spinning in less than 90°	A
Cascade occurs	No	A	No	A
<b>19. B-line stall</b>	<b>A</b>			
Change of course before release	Changing course less than 45°	A	Changing course less than 45°	A
Behaviour before release	Remains stable with straight span	A	Remains stable with straight span	A
Recovery	Spontaneous in less than 3 s	A	Spontaneous in less than 3 s	A
Dive forward angle on exit	Dive forward 0° to 30°	A	Dive forward 0° to 30°	A
Cascade occurs	No	A	No	A
<b>20. Big ears</b>	<b>A</b>			
Entry procedure	Dedicated controls	A	Dedicated controls	A
Behaviour during big ears	Stable flight	A	Stable flight	A
Recovery	Spontaneous in less than 3 s	A	Spontaneous in less than 3 s	A
Dive forward angle on exit	Dive forward 0° to 30°	A	Dive forward 0° to 30°	A
<b>21. Big ears in accelerated flight</b>	<b>0</b>			
Entry procedure	not available	0	not available	0
Behaviour during big ears	not available	0	not available	0
Recovery	not available	0	not available	0
Dive forward angle on exit	not available	0	not available	0
Behaviour immediately after releasing the accelerator while maintaining big ears	not available	0	not available	0
<b>22. Behaviour exiting a steep spiral</b>	<b>A</b>			
Tendency to return to straight flight	Spontaneous exit	A	Spontaneous exit	A
Turn angle to recover normal flight	Less than 720°, spontaneous recovery	A	Less than 720°, spontaneous recovery	A
Sink rate when evaluating spiral stability [m/s]	19		26	
<b>23. Alternative means of directional control</b>	<b>A</b>			
180° turn achievable in 20 s	Yes	A	Yes	A
Stall or spin occurs	No	A	No	A
<b>24. Any other flight procedure and/or configuration described in the user's manual</b>	<b>0</b>			
Procedure works as described	not available	0	not available	0
Procedure suitable for novice pilots	not available	0	not available	0
Cascade occurs	not available	0	not available	0
<b>25. Comments of test pilot</b>				
Comments	Steep spiral, we can archive 26 m/sec with neutrality spiral. At 14 m/sec, the glider recovery the normal flight without intervention and without any neutrality tendency.			