



Flight and Load test report - EN 12491:2001

Manufacturer APCO Aviation Inc.
Address 7, Chalamish St., Industrial park
 38900 Caesarea
 Israel

Certification number: EP 057.2012
Type/model: MD GMD LT
Total weight in flight: 130 kg

Description of tests	place:	date:	result:
1. Deployment system strength test A load of 700 N between each components	Villeneuve	05.08.2009	OK
2. Speed of opening test - ref. A (2 times) Time from the instant of free drop until a load of 200 N is sustained Opening time Opening time	Villeneuve Villeneuve	01.11.2011 28.02.2012	< 5 seconds < 5 seconds
3. Descent rate and stability test - ref. A and B (2 times) The paraglider is released as the parachute begins to open, minimum 100 m descent. Stability 1 Sink rate 1 Stability 2 Sink rate 2	Villeneuve Villeneuve Villeneuve Villeneuve	01.11.2011 01.11.2011 28.02.2012 28.02.2012	Stable 4.57 m/sec Stable 4.93 m/s
4. Strength test 40 m/s opening shock (2 times) The drop test device is accelerated to a straight line velocity of 40 m/s and the parachute deployment handle activated using a static line attached to a drogue chute. Speed of opening is less than 5 seconds Test 1 Test 2	Illarsaz Illarsaz	15.11.2011 15.11.2011	OK OK
5. Interaction and stability test (piloted) - ref. C a the emergency parachute is deployed from a paraglider in normal straight flight. b the pilot shall take no action while the behaviour of the parachute and paraglider are observed 200 metres. c the pilot take action while the behaviour of the parachute and paraglider are observed 200 metres.	Villeneuve Villeneuve Villeneuve	28.02.2012 28.02.2012 28.02.2012	OK OK OK

The model described is in conformity with the flight and load tests carried out by Air Turquoise SA.



For Air Turquoise SA

Alain Zoller

Air Turquoise SA
 Route du Pré-au-Comte 8
 Case postale 10
 CH- 1844 Villeneuve
 email: info@para-test.com



homepage: www.para-test.com

Weather data, ref. 3 and B

Date / place	hPa	wind	temp	humidity
01/11/2011 Villeneuve	970	0	15	69.0%
	<i>Corrected mass:</i>			
	124.45			
28/02/2012 Villeneuve	978	0	9	72.0%
	<i>Corrected mass:</i>			
	133.07			

Reference

A. At horizontal airspeed 8 m/s and vertical speed 1.5 m/s

B. Formula to be used for correcting the test mass of differences from ICAO standard atmosphere

$$m_{\text{corr}} := m_{\text{dec}} \cdot \frac{p \cdot T_0}{p_0 \cdot T}$$

Ground level atmospheric pressure at the test location: (p)

ICAO standard atmospheric pressure at MSL: (p₀)

Ground level temperature at the test location: (T)

ICAO standard temperature at MSL: (T₀)

Total weight in flight: (m_{dec})

Corrected mass: (m_{corr})

C. Only parachute with controls for steering and landing flare



Air Turquoise SA

Route du Pré-au-Comte 8
 Case postale 10
 CH - 1844 Villeneuve
 Switzerland
 mobile: +41 79 202 52 30
 Tel. no : +41 21 965 65 65
 email: info@para-test.com
 homepage: www.para-test.com

For Air Turquoise SA

Alain Zoller

